

ELECTRODE DRYER TYP SET - 1



- **ROBUST CONSTRUCTION**
- **CAPACITY 5kg**
- **TEMPERATURE 100°C**
- **120 Watt HEATING POWER**
- **WITH ELECTRODE BASKET**
- **HEAT BUFFER**

Technical Data

Capacity 5 kg

Input voltage 230V

Power output 0,12 kW

Temperature
max 100°C

Dimensions H/W/D
585 x 150 x 180

Weight 7kg

Order number

845994

The DRYFAST SET - 1 welding electrode dryer is the ideal device for the construction site.

With a capacity of one packet of electrodes and the double-walled insulated housing made of powder-coated and galvanised sheet steel, it is always ready for immediate use.

The temperature of 100°C is reached at a room temperature of approx. 20°C.

The electrode heater is equipped as standard with an electrode carrying basket for easier removal of the rod electrodes.

The electrode dryer of SET - 1 series are equipped with a 230V connection cable with a Schuko plug.

Ventilation of the moisture-saturated atmosphere is ensured via the exhaust air duct on the lid.

All these features make the SET - 1 the ideal appliance for the construction site.

All technical specifications are target values.
Dryfast GmbH & Co. KG reserves the right to change them without prior notice.
No liability is accepted for damage resulting from use.

Dryfast GmbH & Co.KG
Domänenstr. 38
D-44225 Dortmund
Phone +49 (0) 231 – 72 73 865
Mail info@dryfast.de
Internet www.dryfast.de