

ELEKTRODE DRYER TYP WED 1 / 350

Technical Data

Capacity 10 kg

Input voltage 230V

Power output
0,45 kW

Temperature
max 350°C

Dimensions H/W/D
610 x 155 x 161

Weight 8kg

Order number
201350

All technical specifications are target values.
Dryfast GmbH & Co. KG reserves the right to change them without prior notice.
No liability is accepted for damage resulting from use.



- **ROBUST CONSTRUCTION**
- **CAPACITY 10 kg**
- **VARIABLE ADJUSTABLE
100°C – 350°C**
- **450 Watt
HEATING POWER**
- **CENTRAL CHIMNEY**
- **WITH ELECTRODE
BASKET**
- **HEAT BUFFER**

The Dryfast welding electrode dryer WED 1/350 is the ideal model for mobile as well as workshop applications in the field of re-drying.

Thanks to the infinitely variable thermostatic control, the WED 1/350 electrode dryer is extremely versatile.

The robust, double-walled and well-insulated housing is made of powder-coated and galvanised sheet steel.

The WED 1/350 is supplied with an electrode lifter as standard. The lifter is used for easy filling and removal of the electrodes.

The electrode dryer in the WED 1/350 series are equipped with a 230V connection cable with a Schuko plug.

The innovative design with the central-vertical radiator ensures good temperature distribution.

Ventilation of the moisture-saturated atmosphere is ensured via the exhaust air duct on the lid.

The combined support and carrying handle allows the user to utilise the electrode oven as an electrode tubular on the construction site.

All these features make the WED 1/350 the ideal device for construction sites and stationary applications.

Dryfast GmbH & Co.KG
Domänenstrasse 38
D-44225 Dortmund
Phone +49 (0) 231 – 72 73 865
Mail info@dryfast.de
Internet www.dryfast.de